


G-4263



Green Pin® Wide Mouth Towing Shackles bow shackles with safety bolt

- **Material** : bow and pin alloy steel, Grade 8, quenched and tempered
- **Finish** : hot dipped galvanized
- **Certification** : at no extra charges this product can be supplied with a works certificate and/or certificate of basic raw material
- **Note** : only to be used for towing!

diameter bow	diameter pin	diameter eye	width eye	width inside	length inside	width bow	length	length bolt	width	thickness nut	minimum breaking load	weight each
a	b	c	d	e	f	g	h	i	j	k	tons	kg
38	42	89	38	106	216	159	319	248	235	19	132	12.5
45	50	104	45	127	248	175	370	296	265	24	180	18
50	57	111	50	146	273	207	411	338	307	27	240	25
65	70	145	65	165	314	213	487	389	343	33	330	48
75	83	163	75	184	330	254	530	432	404	40	600	70

In inch

diameter bow	diameter pin	diameter eye	width eye	width inside	length inside	width bow	length	length bolt	width	thickness nut	minimum breaking load	weight each
a	b	c	d	e	f	g	h	i	j	k	tons	lbs
1 1/2	1 5/8	3 1/2	1 17/32	4 3/16	8 1/2	6 9/32	12 9/16	9 3/4	9 1/4	3/4	132	27.56
1 3/4	2	4 1/8	1 25/32	5	9 3/4	6 7/8	14 9/16	11 11/16	10 7/16	15/16	180	39.68
2	2 1/4	4 11/32	1 31/32	5 3/4	10 3/4	8 5/32	16 3/16	13 5/16	12 1/8	1 3/32	240	55.12
2 1/2	2 3/4	5 3/4	2 9/16	6 1/2	12 3/8	8 3/8	19 3/16	15 5/16	13 1/2	1 5/16	330	105.82
3	3 1/4	6 7/16	2 15/16	7 1/4	13	10	20 7/8	17	15 7/8	1 19/32	600	154.32